

FLASH CURE UNITS REDFLASH

High wattage and coil density heater, for greater heater surface consistency.

And now with the Vastex cooling fan and air curtain, Vastex flashes can be set closer to the work which increases efficiency and productivity.



**15 YEAR
HEATER WARRANTY**

REDFLASH
18" sqShown with Standard Stand

CE CERTIFIED
BY CERTIFICATION EXPERTS
THE NETHERLANDS

R-18-240

R-18-240-HO

R-1824-240

Heater Size	18" x 18" (46 x 46cm)	18" x 18" (46 x 46cm)	18" x 24" (46 x 61cm)
Power (Wattage)	2,600w @ 240v	3,500w @ 240v	3,500w @ 240v
Power Plug	NEMA 6-15P**	NEMA 6-20P**	NEMA 6-20P**

Features

RELIABLE 15 Year Heater Warranty
POWERFUL 2600 or H.O. 3500 Watt heater (3500 standard 1824)
USER FRIENDLY Diagnostic pilot lights & heat control
CONVENIENT Heavy duty side handles & locking casters


EFFICIENT High wattage and high heater density
FASTEST HO heater flashes plastisol in as little as 4sec
UNIQUE Head leveler, cooling fan and air curtains.
THIN PROFILE Ultra slim 2.75" (7 cm) height head

Options



AutoFlash

Super Heavy Duty Stand



Rotary Table

** Domestic plugs listed. International cords available.



RedFlash_0415

Flash Cure Units



TUV-ISO 9001-2000
Compliant

Technical Specifications

	F-100	F-1000	REDFLASH		AIR-FLASH	
Models	F-100	F-1000	R-18-240	R-1824-240	RA-18-HO	RA-1824
Heater Warranty	15 Year	15 Year	15 Year	15 Year	15 Year	15 Year
Bumper to Bumper Warranty	3 Year	3 Year	3 Year	3 Year	3 Year	3 Year
Heater Size	16" x 16" (41 x 41 cm)	18" x 18" (46 x 46 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)
Unit Warm Up Time	15 min. (120V) or 10 min. (240V)	20 min. (120V) or 10 min (240V)	6 min.	12 min.	6-10 min	6-10 min
Heater Wattage	1625 Watt Heater	1950 Watt Heater	2600 or 3500 Watt Heater	3500 Watt Heater	3500 Watt Heater	4300 Watt Heater
Electrical Specs* / included plug (Some models require a dedicated line. 50/60 HZ for all units.)	120V/13A/1625W NEMA 5-15P 240V/6.5A/1625W NEMA 6-15-P	120V/15.6/1950W NEMA 5-20P 240V/7.8A/1950W NEMA 6-15-P	240V/9A/2600W NEMA 6-15P 240V/16A/3500W NEMA 6-20P	240V/16A/3500W/ NEMA 6-20P Plug	240V/16A/2500W NEMA 6-10P	240V/19A/4300W/ NEMA L6-30P
Electrical Specs - AutoFlash / included plug	110-125V/1A/NEMA 5-15P 220-240V/1A/NEMA 6-15P					

Shipping Weights and Dimensions

	Weight**	Dimensions**
F-100 (Head and Stand)	39 lbs (18 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)
F-1000 (Head and Stand)	42 lbs (19 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)
R-18-240 (Head Only)	35 lbs (16 kg)	26" x 29" x 7" (66 x 74 x 18 cm)
R-1824-240 (Head Only)	43 lbs (19.5 kg)	26" x 35" x 8" (66 x 90 x 20 cm)
RA-18-HO (Head Only)	64 lbs (29 kg)	29" x 26" x 15" (74 x 66 x 38 cm)
RA-1824 (Head Only)	74 lbs (35.5 kg)	35" x 29" x 15" (89 x 74 x 38 cm)
AF-120/AF-240 AutoFlash kit	51 lbs (25 kg)	31" x 22" x 14" (79 x 56 x 36 cm)
SH-STAND-WS Standard Stand for Manual Flash	22 lbs (10 kg)	37" x 7" x 3" (94 x 18 x 8 cm)
SHHD-STAND-M Heavy Duty Stand for Manual Flash	42 lbs (19kg)	30" x 14" x 7" (76 x 35.5 x 18 cm)
SH-LEGS-AF Standard Stand for AutoFlash	15 lbs (7 kg)	37" x 7" x 3" (94 x 18 x 8 cm)
SHHD-STAND Heavy Duty Stand for AutoFlash	39 lbs (18 kg)	30" x 15" x 11" (76 x 38 x 28 cm)

NORTH AMERICAN POWER PLUG CONFIGURATION		
RECEPTACLE		PLUG
	120V	
NEMA 5-15R		NEMA 5-15P
	240V	
NEMA 5-20R		NEMA 5-20P
NEMA 6-15R		NEMA 6-15P
NEMA 6-20R		NEMA 6-20P
NEMA 6-30LR		NEMA 6-30LP

1 in = 2.54 cm
1 lb = 0.454 kg

*If extension cord is required, consult a licensed electrician.

**All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications.

